O = Corner monument restored.

Index No.E-6-7

CPI-1977

History of original corner establishment:

No record of any previous survey.

Description of corner evidence found:

No evidence of any corner recovered. Corner established by proportional measurement. Ran traverse between previously established 1/4 corner and W 1/16. Computed distance 1329.522 feet at bearing N 87° 48' 11" E. Set 1/32 corner at 664.761 feet (10.072 chains) intermediate.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set 1½" iron pipe with 2" brass cap, projecting 24" above ground. Cap stamped:

Marked NBTs - Sugar 10" S14°E, 5.6 links, scribed 1/32 BT.

Sugar 8" N64°W, 19.6 links, scribed 1/32 BT.

T35N R12E

1/32 5 5

Dated at	Rhinelander	, Wis., this	19th	day of	August	, 19.77
Signature.	County Surveyor, Register	Title ed Land Surve	Registered yor, or other duly	Land Surveyon authorized official)	or Regi	istration No. <u>S-498</u>
Omce of Keg	gister of Deeds, County of		22nd		, I HULCH	cci cii y ciiac ciic witiii
at 3:30 o	clock P. M. (Register of Deeds	inul	• •			112154
Bv	(Register of Deeds	s) //	Deputy			