State of Wisconsin

Philip T. Hansen , do hereby

certify that on the 28th day

corner of Sec. 8, 9, 16 & 17

Township......35......, North, Range

established Section 19.77, Ixfaund Section

County of Forest

## O = Corner monument restored.

## CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

Original corner established by Hiram Fellows, Deputy Surveyor, in 1859. No records of any subsequent survey.

Description of corner evidence found: No evidence of any corner recovered. Found remains of an old fence line running south.

Corner established by proportionate measurement from previously established 1/4 corner between Sec. 7 & 18, measured distance by traverse to a R.R. spike in centerline of Highway "B" with fence line running north and south. Computed distance was 21.16963 chains at bearing N 84° 36' 46" E. Doubled this distance and set section corner which point fell in 9 line with old fence line south and a woods line to north.

Description of monument and accessories I established to perpetuate the original location of this corner.

Drove a R.R. spike in south edge of Highway "B" and set a 2½" Berntsen A-1 Federal Monument 50 links south as witness corner. Stamped:

Monument projects 1" above ground.

Marked NBTs from true corner. Sugar 5" S54W, 107.5 links Sugar 8" S26 W, 89.4 links Sugar 8" S25 E, 90.9 links, scribed SC BT.

T35N R12E 5498 - 1977N 50 1ks to Cor.

Dated at	Rhinelander	, Wis., this.	3rd	day of	October	<b>,</b> 19	
	Hillip Hensen. (County Surveyor, Regis						
Office of R	egister of Deeds, County of was filed in this office for	fthe	Forest <b>7th</b>		I hereby certif	fy that the within	
at 2:45 o'clock P. M.  Lugen States M.  (Register of Deeds)					DOCUMENT Number 112527		
Bv	(Register of De	eeds	Depu	ıty			