

232901

JAN 08 2021

Time: 10:00 A.M.
Vol.: Corner Restoration
Page Number: 6-13

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

NOTE: This form is intended and designed to fulfill all requirements of Wisconsin Administrative Code, Chapter A-E 7.08 U.S. Public Land Survey Monument Record. An additional sheet may be added if necessary to conform with said requirements.

CORNER LOCATION:

West Quarter Corner of Section 10
Township 35 North, Range 13 East of the 4th P.M.
Town of Lincoln, Forest County, Wisconsin

ROMPORTL ID NUMBER:

43513092000

FOREST COUNTY COORDINATES:

(NAD83/2011)

N: 555,867.647

E: 846,535.200

HISTORY OF ORIGINAL CORNER:

ORIGINAL SURVEYOR: James L. Nowlin
DATE OF SURVEY: September 1865
ORIGINAL ACCESSORIES: 46" Birch, N35°W, 25 lks
30" Sugar, S18°E, 23 lks

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

T35N - R13E

DESCRIPTION OF MONUMENT FOUND AT THIS CORNER AND IF IT WAS ACCEPTED, STATE ALL EVIDENCE (MATERIAL, TESTIMONIAL, OCCUPATIONAL, PLATS, RECORDS, OTHER MONUMENTS) USED AS A BASIS FOR ACCEPTING. IF NOT ACCEPTED OR IF NOTHING WAS FOUND, STATE EVIDENCE USED AS BASIS FOR ESTABLISHING LOCATION. IF RE-ESTABLISHED THROUGH LOST CORNER PROPORTIONATE METHODS, INDICATE ALL MONUMENTS, DISTANCES AND DIRECTIONS USED TO ESTABLISH. INDICATE TYPE OF MONUMENT AND SIGN POST FOUND OR SET.

1940 - C.E. Walker set a 2" Iron Pipe 5' long with Brass Cap offset 25.0 feet west of corner.

9/15/1975 - Thomas R. Amott found 2" Iron Pipe set by Walker and set a 1 1/4" Iron Pipe at location of corner 2" below road grade. He also set out one additional tie.

10/29/2020 - Visited corner location and did not find evidence of monument. I found the 2" Iron Pipe with Brass Cap set by Walker as well as Blazed Maple to Southwest and used them to determine position of corner. I set an 1.0" X 30" Iron Bar at the corner location and set out new ties as shown below.

PLAN VIEW OF CORNER WITH TIES TO AT LEAST 4 WITNESS MONUMENTS. IF IN DISAGREEMENT WITH PREVIOUSLY ESTABLISHED CORNER, SHOW THE DISTANCES BETWEEN THE TWO CORNERS AND ALSO INDICATE THE TIES TO THE DISPUTED.

Set 3/4" Rebar
and set Bearing
Tag on 12" Maple

N21° 49' 03"W
72.38'

Quade Lane

Gravel Pullout

S89° 35' 56"W
25.00'

Found 2.5" Iron Pipe
with Brass Cap

Found 18" Maple
with Blaze: Set
Bearing Tag

S41° 31' 14"W
23.00'


Gravel Drive

Set 1.0" X 30" Iron Bar

Set 3/4" Rebar
and set Bearing
Tag on 5" Maple

N27° 43' 28"E
52.38'

SCALE: 1" = 20'
Bearings Forest
County Grid



I, John M. Jursa, Professional Land Surveyor No. S-3201, hereby certify that the corner location on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

John M. Jursa, PLS No. S-3201
STEIGERWALDT LAND SURVEYING, LLC

43513092000

1/5/23 re-scanned to reflect correct recording date 1/8/2021 CBJ/CPD.

6-13