CERTIFIED	IAND	CORNER	RESTORATION
CEVILLIED	FWIND	CORNER	KESTUKATIUN

History of original corner establishment:

Sept 11 - Sept 21, 1865 Original subdivision by James Nowlin

15 Lks. Hemlock NI6E Hemlock :

Description of corner evidence found:

2" iron pipe 5' long with brass cap offset 20 feet north set by C.E. Walker in 1940

Description of monument and accessories I established to perpetuate the original location of this corner.

Reset corner with RR spike Left monument set by Walker

Ties:

Walker monument 20.00 feet Power Pole (3513-22W8) S40E 31.07 feet

ZZZZZZZZZ	SCON	STAIN.
	THOMAS R. ARNOTT	THE WAY
*	\$-887	*
	WIS.	
	SURVE	NEWSTAN.

Dated at	Crandon	. Wis., this	29th	day of	October	19.75
7	1					

Signature Thomas R. Auco H Title Land Surveyor Registration No.S=887.... (County Surveyor, Registered Land Surveyor, or other duly authorized official)

Office of Register of Deeds, County of Forest , I hereby certify that the within at 1 o'clock P. M.

Eugene Statesny (Register of Deeds)

Document Number

O = Corner monument restored.

State of Wisconsin

I-Thomas R. Arnott do hereby

certify that on the 16th day

of September 19.75., I found

corner of sections 15, 16, 21 & 22

13 E., Fourth Principal Meridian,

as described hereon; and that from this evidence

I established a new monument and accessories

as described hereon to perpetuate the original

County of Forest

location of this corner.

Herbert Wagoner

Resident witnesses:

evidence of the saction.

SS.