O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. 0 - 12

History of original corner establishment:

012

Corner established by C. Walker.

Recovered and remonumented by Thomas Arnott, Registered Land Surveyor.

Description of corner evidence found:

Corner established by subdivision of the NE 1/4. Location of NE 1/16 is \$88-54-13E 1308.95 feet of NC 1/16 and N2-01-58E 1308.94 feet. of EC 1/16.

Description of monument and accessories I established to perpetuate the original location of this corner.

Our corner position falls south 3.50 feet of old NE 1/16 corner. Upon Thomas Arnott permission, we removed present monument and placed in our position the 2-1/2" A-1 monument stamped:

•	NE 1/16
Marked NBT's:	
Sugar 7" N51W 18.32 feet	s 21
Sugar 7" N50E 29.60 feet	Forest County

Dated at	Rhinelander	, Wis., this	30th	dav	v of	December	. 19 82	
Signature	Min Barler	Title Re	gistered	Land	Surveyor		ation No. S-1682	
(County Surveyor, Registered Land Surveyor, or other duly authorized official)								
Office of Re	egister of Deeds, County of was filed in this office for rec	Forest		72	······	I hereby ce	rtify that the within	
instrument	was filed in this office for rec	ord on the	TOT	n	.day of	February	y 19 <u>83</u>	
at10:30	o'clock				,		•	
2	Lot -	,			DOCUMEN	ON TI	122912	
. Lun	(Register of Pleed	suf-						
(/		~ (<i> </i>					•	