6' Balsam Fir

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

Corner to Section 31,36 T 35 N, R 13E Quarter (Section/Quarter) F R JAE R₁₃E SECTION 51 SECTION 3 Marked boundary line of USFS lands

O = Corner monument restored.



Corner consists of a 1" iron pipe with aluminum cap stamped for corner. Ties are to aluminum nails driven into tree centers which trees were blazed and scribed.

> 1-2 N 30° E 28.50' 1-3 S 65° W 2.30 1-4 N 75° W 5.55

7" Balsan Fir sign post morth 0.65' Balsam Fir

Certificate Ready For Filing:

Kim H Pritzlaff, RLS No. 1259 (Type or print name) certify that the corner location shown on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the

best of my knowledge and belief.

Signature

1993

Date

History of original corner establishment, record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence, and what you found and how the monument was set.

In 1857 Alfred Millard, contract surveyor, set this corner at 40 chains and marked the following bearing trees:

Yellow Birch 14" Maple

W88*M* 14"

N88E

42 links

In 1964 Neal Sperhake, RLS Set a 1" iron pipe with aluminum cap stamped for corner at this corner location.

I found Sperhake's monument in good condition surrounded by heavily logged Popple slashing. I set his corner to USFS standards as shown below. The monument fell with an accuracy of one part in 4,092 which was within tolerances of the 1964 period of one part in 3000.

In the plan view drawing below, provide reference ties to at least 4 witness monuments, or, if the location is within a municipality, to at least 2 witness monuments. (Witness monuments shall be made of concrete, natural stone, iron or other equally durable material, except wood other than bearing trees.) Also, show any material discrepancies between the corner restored or re-established and the location of any other previous corner location or occupation.

MAINTENANCE RECORD

^!: <u></u>		•		
Condition of Ties	· · · · · · · · · · · · · · · · · · ·			
New Ties, if any:		•		
• •	•	•		
			·	
	•	•		•
Date		Signature		
- •				
Condition of Monument			-	
•	- -		•	•
Condition of Ties				
New Ties, if any:	-		· •	
	•			
•		· ·	- - •	
	•			
		• •		
		•		
Date	· · · · · · · · · · · · · · · · · · ·	Signature		
	·		· ·	
		•	•	
Condition of Monument		•	•	•
Condition of Ties		-		
New Ties, if any:				
-				

Date

Signature

REGISTER'S OFFICE FOREST COUNTY, WIS.

NOV 2 3 1995

State of Wisconsin County of FOREST	ss. RESTORATION OF LOST ORIGINAL GOVERNMENT SURVEY CORNER.
I NEAL SPERHAKE	, do hereby certify that on the TWENTY-EIGHTHday of JULY the EAST QUARTER SECTION CORNER OF SECTION 36, TOWNSHIP 35 NORTH, RANGE al Meridian, as described hereon.
History: This corner was	established during the original survey of this township, as noted in leld notes for the original survey of T35N-R13E, 4th. p.m.
At the point determined GALVANIZED IRON PIPE, THE "KIMBERLY CLARK CORP. The pipe is witnessed by	and accessories I established to perpetuate the location of this corner: for the location of the corner I emplaced a: REEE FEET LONG, ONE INCH IN DIAMETER, WITH ALUMINUM CAP DENOTED AS, T35N 4 BTWN. 36 & 31 R13-14E SPERHAKE RLS 463 7/28/64." 7: 10. 11. 12. 13. 14. 15. 16. 16. 16. 16. 17. 18. 18. 18. 18. 19. 19. 19. 19. 19. 10. 10. 10. 10. 10. 10. 10. 10. 10. 10
Description as to how o	corner was located: No evidence of the original corner present. Thus, set the corner by proportionate measurement. The section corners $\frac{1}{2}$ mile north and south, respectively, have been previously established with a distance between them of 79.50 chains. Thus, set the quarter corner 39.75 chains from either corner and on a straight line between them.
O = Corner momment restored	SS622 FOREST COUNTY, WIS. JAN 121955 Grand Grand Register of Par
	Resident witnesses Dated at Crandon , Wisconsin, this 12th day of January , 1965 . Signature
Surveyor's Seal	Title Registered Land Surveyor Registration No. 463 **Office*** Forest County of Wisconsin I hereby certify that the within instrument was **INSON XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

4351336200

Title Notary Public