I Philip T. Hansen , do hereby certify that on the 12th day of December , 19.74 , I found evidence of the N-1/16 corner of S12-S7 Township. 36...., North, Range 11-12 Fourth Principal Meridian, as described hereon; and that from this evidence [ established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Re	esident wi	tnesses:	G.C.O.V.S.		
		,	JI-)~~~~~	HLIP T. HANS ARGONNE WIS.	
<u>σ</u>		<b>T</b> 3	6N	SUR	
S12 N R11F	<b>2</b>	!   S7 !	   R12E 		

O = Corner monument restored.

## CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

Original corner established by B.F. Dorr in 1897. H.C. Lawrence retracement survey of 1956, states that when he ran the range line south from NE corner, Section 12, he recovered the N-1/16 corner 2 links east of his line. He recovered the 1/4 corner 5 links east of his line. No mention was made in Dorr's notes about running the east line of Section 12. The recovered 1/16 corner probably set by someone else. Lawrence set his post at 19.99 chains, equidistant between the section corner and the 1/4 corner.

> Black spruce 5" Black spruce 4" 12½ links 28½ links S60W S60E

Description of corner evidence found:

Recovered H.C. Lawrence's 4" cedar post, squared and scribed S12 N-1/16; S7 N-1/16

Black spruce 5" Recovered  $12\frac{1}{2}$  links Scribed S12 B.T. 29 links Scribed B.T. Black spruce stump

Description of monument and accessories I established to perpetuate the original location of this corner. Set new 1" x 5' galvanized iron pipe with brass cap stamped -

> N.B.T. Black spruce 4" N17W 33 links Scribed 1/16 B.T.

S498

T36N

CPI-1974

Wis., this 12th day of December Dated at.\_\_\_\_

Title Registered Land Surveyor Registration No. S 498 (Lounty Surveyor, Registered Land Surveyor, or other duly authorized official)

Office of Register of Deeds, County of Forest instrument was filed in this office for record on the 17 day of 222 ancho, 19.75. at 3:35 o'clock 6. M.

(Register of Deeds)