O = Corner monument restored.

Index No. V-//

History of original corner establishment:

Original corner established by Wm. E. Dougherty, Deputy Surveyor, in 1859 from which Birch 12" bears S 56 E 20 lks. and Birch 20" bears N 65 W 17 lks. Original distance between Sec. 28 and 33 was 80.64 chains.

Description of corner evidence found:

Ran traverse from Sec. Corner 28-29-32 and 33 to Section Corner 27-28-33 and 34. Computed distance between corners, 84.140 chains at N 83° 49' 30" E. Computed distance to Quarter Corner 42.07 chains. This line follows an old road known as Ison Road.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set 1½" x 18" iron pipe on line at 42.07 chains N 83° 49° 30" E of Section Corner 28, 29, 32, 33. This fell on the South edge of Ison Road. Pipe is 4" below surface.

Set a 2½" Berntsen A-1 Federal Monument for witness corner 25 lks South. Monument projects 18" above ground. Cap stamped.

NBTs - R. Oak 7" S56°W 74.9 lks, scribed 1/4 BT.

Sugar 7" N14°E 88.4 lks, scribed 1/4 BT.

W.C. and BTs painted blue.

N 25 lks to Cor.

Dated at Rhinelander	, Wis., this	21 st	day of	f Ju	ne	, 19 76
						stration No. S-498
Signature Willip Hansen. Title Registered Land Surveyor Registration No. S-498 (County Surveyor, Registered Land Surveyor, or other duly authorized official)						
Office of Register of Deeds, County of		TOTEDO			1 nereby	certily that the within
instrument was filed in this office for reco	ord on the	22 n d	da	y of	June	
at 3:45 o'clock P. M.		TY C		NUMBER .		L09501
Engent States (Register of Deeds						