ERTIFIED	LAND	CORNER	RESTORATION

State of Wisconsin

Forest

I Philip T. Hansen, do hereby certify that on the 29th day of July , 19.77..., I found evidence of the E.1/16. corner of Section 34 & 3 Township...36 & 35......, North, Range 12 East Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Resident witnesses: Glen Barker -PHIFIB--T:---HANSEN Jim Claflin ARGONNE," WIS. Herb Wagoner **S:498** T35N R12E 19.872 19.872

1 E 1/16

O = Corner monument restored.

History of original corner establishment:

No records of any previous survey for this corner.

Description of corner evidence found:

Recovered old stone fence line piled along old fence line north along edge of old fields to east and west. Accepted old fence line as the 1/16 line. Distance from section corner S 88° 59' W to 1/16 corner is 1311.579 ft. (19.872 chains).

Description of monument and accessories I established to perpetuate the original location of this corner.

Set 13" x 18" iron pipe, 2' north of centerline of Sipple Road, 5" below the surface for corner.

Set a 13" iron pipe with 2" brass cap 60 links south for witness corner. Cap stamped: Marked BTs - Sugar 10" S28 W, 77.5 links. S498

Sugar 8" S36 E, 85.3 links, scribed 1/16 BT.

T36N R12E N 60 1ks E $1/16 \frac{s_{135}}{s_{12}}$ W.C.

T35N R12E CPI-1977

Dated at Rhinelander	, Wis., this. 2nd	day ofA	ugust	, 19 <u>.77</u>
Signature Milly Thomsen! County Surveyor, Regis				
County Surveyor, Regis	tered Land Surveyor, or other duly	authorized omeiai)	T 1 1 .*C	.11
Office of Register of Deeds, County of instrument was filed in this office for a	f rorest 22nd		I hereby certify	that the within
instrument was filed in this office for i	record on the	ay oi	W rrm71	, ту

at 3:30 o'clock P_{\bullet} / M.

Measurements and bearings made from true corner.

DOCUMENT NUMBER