<u>9</u>	
98	
ithin .79	
7	

PERTIFIED	LAND	CORNER	RESTORATION
したべいてにし	LWIND	CORNER	VE2 LOVATION

State of Wisconsin County of Forest I Philip T. Hansen do herebertify that on the 22nd day of September 19.79, I four established examples the C. 1/4 corner of Section 6. Township 36 North, Rang 15 East Fourth Principal Meridian as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner. Resident witnesses: Glen Barker PHILIP T. ARGONNE, WIS. Herb Wagoner S. 498				
	T36N R15E			

O = Corner monument restored.

History of original corner establishment:

No records of any previous survey available. No evidence of any corner recovered.

Description of corner evidence found:

Corner established by traverse and computation. Ran traverse from N 1/4 to S 1/4 and E 1/4 to W 1/4 to establish the C 1/4 corner. Computed distance from N 1/4 is 2500.682 ft. at bearing S 2° 04' 20" W, N88° 47' 38" W 2630.73' from E 1/4; North 2° 04' 20" E of S 1/4 and S 88° 47' 38" E 2604.95' from W 1/4.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 2-1/2" Berntsen A-1 Federal Monument with 2" brass cap - stamped:

Monument projects 18" above ground.

Marked NBT's - Maple 8" N53 W 26.30 feet Cedar 9" N18°E 23.28 feet

Cedar 9" N50°E 21.75 feet all scribed C 1/4 BT

T36N R15E $c_{1/4} + \frac{s_{+6}}{}$

5498 - 1979

Dated at Rhinelander , Wis., this 9th day of October Signature Milio Volument Title Registered Land Surveyor Registration No. S-49
County Surveyor, Registered Land Surveyor, or other duly authorized official) Office of Register of Deeds, County of Forest I hereby certify that the wi instrument was filed in this office for record on the 13th day of November, 19... at 8:30 o'clock A. M. DOCUMENT NO.