CERTIFIED LAN	D CORNER	RESTORATION

History of original corner establishment:	
rustory of original corner establishment:	

No evidence of any corner.

Description of corner evidence found:

Corner established by traverse and computation. Total distance from C 1/4 corner section 25 to 1/4 corner between sections 25-31 T37N R13&14E is 2614.86 feet at bearing N89-40-31E. Set EC 1/16 1307.43 feet intermediate.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a $1-1/2$ " iron pipe with brass cap - stampe	d:
Projecting 12" above ground.	
Marked NBT's:	T37N R13E
B.Spruce 10" $\$32^{\circ}W$ 46.95 feet	C. 1/16 S <sub>4-25</sub>
Tamarack 8" \$50°E 22.75 feet	
scribed 1/16 BT	S1537-1980

Dated at R	hinelander	, Wis., this	23rd	day of	June	, 19.81
Signature	Mil K. Pleagel  (County Surveyor, Register)	Title Re	egistered	l Land Survey	or Regis	stration No. 1537
Office of Registe	er of Deeds County of	ed Land Survey For	est	uly authorized omc	iai) I hereby (	certify that the within
instrument was	er of Deeds, County of filed in this office for rec	ord on the	lst	day of	July	19.81
at 8:30 o'clo	ck A. M.  Alme Stal				DOCUMENT	
By.	(Register of Deeds		Depu		12C	027

State of Wisconsin County of Forest Daniel K. Pleoger, do hereby certify that on the 18th day corner of <u>Section 25</u> Township.......37......., North, Range as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate original location of this corner. Resident witnesses: DANIEL FLEOGER

	T37N	R13	
	<b> </b> 		1
	!	 	<u> </u>
	<b> </b> 	EC 1/16	
		¦ €	• •
1			
	<u> </u>	' — — — ·	<u> </u>
	<b>`</b>		
1	· I	· 	

O = Corner monument restored.