

U.S. PUBLIC LAND SURVEY MONUMENT RECORD
FOREST COUNTY

TYPE OF MONUMENT: 3" MAG SURVEY SPIKE
WISCONSIN COUNTY COORDINATE SYSTEM (FOREST)
DATUM: NAD 83 (2011 ADJUSTMENT)
NORTHING 597678.86
EASTING 841217.91
DRAWN BY: ANDREW HUNTER

CORNER INDEX NO. X-9
SECTION 32
TOWN 37 NORTH
RANGE 13 EAST



BASIS FOR MONUMENT LOCATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT AND SUBSEQUENT RESTORATIONS AND DESCRIPTION OF ANY RECORD, MONUMENT, OCCUPATIONAL, TESTIMONIAL OR OTHER EVIDENCE CONSIDERED:

PREVIOUS TIE SHEETS PREPARED BY PHILLIP T. HANSEN DATED NOVEMBER 17, 1977 AND R. JOHNSON DATED FEBRUARY 28, 1992 BOTH CALL FOR A 1/2" X 6" SURVEY SPIKE.

I COMPLETED A FIELD SURVEY PRIOR TO HIGHWAY CONSTRUCTION ALONG S.T.H. "32" AND DID NOT FIND THE CALLED FOR MONUMENT BUT INSTEAD FOUND THE SHAFT OF A MAG NAIL IN ASPHALT.

3 WITNESS TIES WERE LOCATED AND MEASURED AS RECORDED ON THE TIE SHEET THAT WAS PREPARED FOR THE S.E. CORNER OF SECTION 29 BY R. JOHNSON ON FEBRUARY 28, 1992, WHICH WAS BELIEVED TO BE ERRONEOUSLY FILED. THEREFORE THE FOUND MAG NAIL SHAFT WAS ACCEPTED AS THE TRUE CORNER LOCATION. I SET A 3" MAG SURVEY SPIKE AFTER CONSTRUCTION WAS COMPLETED AND SET A MAG NAIL FOR WITNESS TIE AND VERIFIED THE 3 REMAINING WITNESS MONUMENTS.

SEAL:



CERTIFIED CORRECT:

Andrew L. Hunter
PROFESSIONAL LAND SURVEYOR

DATE OCTOBER 14, 2022

TIE SKETCH

SHOW AT LEAST FOUR TIES, ALSO FENCE LINES, ROADS, TOPO, SIZE AND TYPE OF WITNESS TREES AND ANY OTHER PERTINENT SITE DETAILS. IF OFF THE ROAD, THE BEST WAY TO ARRIVE AT THE CORNER.

