Est.	certify that on the September of September of Section Township 37. 13 East For as described hereon; and I established a new more	ss. 24 30 31 30 31 30 30 30 30 30 30
		PLEOGERS-1537
		SURVENDO
	T37N	R13E
	<u></u>	36EC_1/16
	1	

O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. X-24

History of original corner establishment:

No evidence of any previous survey.

Description of corner evidence found:

Total distance from 1/4 corner between sections 36 & 31 T37N R13 & 14E to C 1/4 corner of section 36 is 2617.418 ft. at bearing N88-38-04W. Set EC 1/16 1308.709 ft. intermediate

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1½" iron pipe with 2" diameter brass cap stamped:

Monument projects 18" above ground

Marked NBTs

Black spruce 3" N30W 39.0 ft.

Scribed B.T.

Black spruce 10" N48E 71.17 ft.

Scribed 1/16 B.T.

CPI - 1981

	Rhinelander	-		_			
Signature.	Swell flesgel (County Surveyor, Register	Title red Land Surve	Registered eyor, or other duly	Land authoria	Surveyor ed official)	Reg	istration No.1537
Office of Regionstrument w	ister of Deeds, County of as filed in this office for red clock		Forest		,	I hereby	certify that the within
	(Register of Deed	s)		DOCU	MENT NO	•	121388
By	· 		Deputy				