DOCUMENT NUMBER 107867

History of original corner establishment: Original corner established by James L. Nowlin, Government

Deputy Surveyor, in 1865, from which fir 6" bears N240W 9 links and cedar 6" bears N60°E

10 links. Corner recovered by Ray Leigh, Consolidated forester, about 1940. Recovered

old stake while running line between Sections 2 and 3 following old blazed line. Set new

CERTIFIED LAND CORNER RESTORATION

Description of corner evidence found:

at 3:15 o'clock Pe M

wood squared post and at a later date drove in an iron pipe.

State of	Wisconsin]
County of	Forest	} ss.
D1 111 D	77	

rertify that on the 19th day of September 19.75, I found evidence of the Section corner of S2, S3, S10, & S11

Township 37, North, Range 14 East, Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Resident witnesses:

Glen Barker

HANSEN

Jim Claflin

WIS.

S-498

SURVE

T3/N_RI4E				
_	i	 		
	' !	' 	<u>-</u> – – –	
]	- 		
	l I	! 3 !		
_	¦	!	<u>.</u> – – –	
		l I	 	
ı	 <u> </u>	l '] <u></u>	
		l	1	
	1	 	1 I	
		· 		

O = Corner monument restored.