121099

DOCUMENT NO.

al ,	Total distance from section corner 35, 36, 1, 2 T36 and 37N R14E to 1/4 corner between sections 35 and 36 is 2873.269 ft. at bearing N1-00-47W Set S1/16 1436.634 ft. intermediate
	——————————————————————————————————————
	Description of monument and accessories I established to perpetuate the original location of this corner.
	Set a 1½" iron pipe with 2" diameter brass cap stamped: Monument projects 18" above ground. Marked NBTs: Sugar 7" S25E 20.73 ft. Hemlock 10" N69E 44.18 ft. Scribed 1/16 - BT Scribed 1/16 - BT S1537 T37N R14E S1/16 35 36 C.P.I 1981
_	Rhinelander , Wis., this 3rd day of November , 1981
	Signature Oovel K. Pleager Title Registered Land Surveyor Registration No. 1537 (County Surveyor, Registered Land Surveyor, or other duly authorized official)
_	Office of Register of Deeds, County of <u>Forest</u> , I hereby certify that the within instrument was filed in this office for record on the <u>19th</u> day of January 19.82

CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

Description of corner evidence found:

at 3:00 o'clock P. M.

Engene States of Geeds)

No evidence of any previous corner.

 State of-Wiscon 	sin } }ss.
- State of-Wiscon County of Forest	} ss.
I Daniel K. Pleoge	er do hereby
I Daniel K. Pleoge certify that on the of September	day
evidence of theS	L/16
corner of Sections	35 & 36
Township 37 14 East Fourt	North, Range
14 East Fourt	h Principal Meridian
as described hereon; and th	_
I established a new monu	
as described hereon to pe	erpetuate the original
location of this corner.	MISCONS
	WI THE WAY TO VE TO THE PARTY OF THE PARTY O
Resident witnesses:	DARIEL
	DANIEL
\$\dag{2}	PLEOGER
9 6	S-1537
	WINTER, WIS.
Resident witnesses:	
	SOUND ASSESSED OF
	~~@ÜÜÜ <i>Baa</i> ~
ı	

T37N R14E S 36 × S 1/16

O = Corner monument restored.