CE	RTIFIED LAND CORNER RESTORAT	TION
State of Wisconsin		
State of Wisconsin State		
I found evidence of the North	theast Section corner of Range 13 East Fount for Range 13 East Fount for Range 13 East for Section for Range 13 East for Section for Secti	Section 30 rth Principal Meridian, as described
Dependent Resurvey in 1942 Located corner by proportion Set a concrete monument, 24	onal position. 4 inches long, 4 inches in diameter, R13E, S19, S20, S30, S29, 1942 8s. L lks. 57 lks.	er,
Description of corner evidence for	ınd:	
Monument as described above Hemlock 18, S70E, 66.7 feet Maple 19, S81W, 37.6 feet Maple 14, Snag, N54W, 64.7 Corner is in bottom of small	t feet	
December of measurement and acc	essories I established to perpetuate the lo	cation of this corner
Blazed and scribed the fol White pine 5, N41E, 16.83 White pine 6, S5E, 48.02 f Set steel sign post 0.5 fe	lowing new bearing trees: feet eet	JEAN F. RESVICK RHINELANDER, WIS.
	Resident witnesses	SUR
Sec. 30	Dated at Rhinelander Wise 19.79 Signature Jean F. Resvick (County Surveyor, Registered Land Surveyor)	
	(County Surveyor, Registered Land Surve Surveyors Registration No. S-802	yor, or other duly authorized official) DOCUMENT NO. 118087
	Office of Register of Deeds I hereby certify that the within instrume	County of Forest
- Corner monument restored	on the 9th day of June No. Page No. Signature Sharon Mueller	1980, and was filed in Book
	e. 13 East , Section 30 , Ind	