LANGLADE COUNTY SECTION INFORMATION SHEET BY: wisconsin valley surveyors DATE: 12-27-99	SECTION 34 T 34 N., R 12 E. N RECORD # 10524 LANGLADE COUNTY SURVEYORS OFFICE DATE FILED: \$\frac{125}{00}\$ BY: \textsquare{1}\$ Directly	34-9 34-10 34-11 34-12
NAIL SET NAIL FOUND RR SPIKE SET RR SPIKE FOUND IRON PIPE SET (SIZE 14") IRON PIPE FOUND (SIZE 1") capped 2" iron pipe with brass cap 1½" iron pipe with galv. cap 3" Aluminum Mon. with cap IT WILL BE ASSUMED THAT ALL DIMENSIONS SHOWN ARE COMPUTED DIMENSIONS, UNLESS	2697 101	72-13 32-14 33-P 33-10 33-11 33-12 33-12 33-14 34-P
THEY ARE MARKED: "(D)" WHICH STANDS FOR DIRECT MEASUREMENT. FOR US TO USE THE DIRECT MEASUREMENTS IN A LEAST SQUARES ADJUSTMENT, PLEASE COMPLETE THE FOLLOWING: THEODOLITE ACCURACY 20 ^M MANUFACTURERS EDM ACCURACY SPECIFICATION +- 5 mm + 5 ppm TRAVERSE TARGETS (CIRCLE ONE) ON TRIBRACHS HANDHELD BOTH DIRECT ANGLES WERE TURNED Z TIMES DIRECT DISTANCES WERE MEASURED (CIRCLE ONE): ONE DIRECTION TWO DIRECTIONS	S87°29'09"W 5407.96' 2724. 51' 2683 .45' E	11-14 31-15 32-10 32-11 32-12 32-11
COMMENTS: DAVID J. GOSLIN S-2280 WAUSAU, WI SURVENIMENTALINATION WI SURVENIMENTALINATION	1177.15 ¹	30-11 30-12 31-6 31-10 31-11 31-12 31-13 3