O = Corner monument restored.

Index No.

History of original corner establishment:

Original corner established by James L. Nowlin Gov. deputy surveyor in 1865 from which sugar 8" bears N54W 6 lks and hemlock 7" bears S62E 25 lks.

Description of corner evidence found:

Total distance from section corner 5-6-7-8 to section corner 4-5-8-9 is 5226.064 ft. at bearing N89-25-27-E.

Set 1/4 corner 2613.032 ft. intermediate

Description of monument and accessories I established to perpetuate the original location of this corner. Set a $2\frac{1}{2}$ aluminum A-1 federal monument with alloy cap stamped:

Monument projects 12" above ground. Marked N.B.T.s.

Maple 5" N54E 9.96 ft.

Black ash 5" S26E 8.93 ft. Black ash 4" N58W 15.58 ft.

Scribed 1/4 - B.T.

T34N R13E

1/4 s 5 8 8

S1537 -1981

Engene Saltgenss (Register of Deeds)				120517
& 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1	,			CUMENT NO.
Office of Register of Deeds, County of instrument was filed in this office for record 2:00 o'clock P. M.				,
instrument was filed in this office for reco	rd on the 25	th day	of September	1981
Office of Register of Deeds, County of	Forest		, I hereby cer	rtify that the withir
Signature Omio L. Pleager Title Registered Land Surveyor Registration No. 1537 (County Surveyor, Registered Land Surveyor, or other duly authorized official)				
Signature Camil K. Pleager	Title Regis	tered Land	Surveyor Registr	ration No. 1537
	·	•		_
Dated at Rhinelander,	Wis. this 17	'day of	September	1981