State of Wisconsin

County of Forest

I Philip T. Hansen do hereby

CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

Original corner established by J.L. Nowlin, Deputy Surveyor, in 1859.

No records of any subsequent survey.

Description of corner evidence found:

Corner alighment obtained from intersection of the centerline of Walnut Hill Road, (N-S), the north edge of an old field with old rock fence (west) and an old section line road to the east.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a $1\frac{1}{2}$ " x 18" iron pipe at intersection in road bed surface. Top of iron pipe set 4" below surface.

Set a 23" A-1 Federal Monument 50 lks west for witness corner, cap stamped Pipe projects 18" above ground.

NBTs - Sugar 8" N50°E 84.3 lks, scribed SC BT.

Sugar 6" S57°E 65.8 lks, scribed SC BT.

Sugar 10": N74°W 115 lks, scribed SC BT.

Bearings and distances to true corner. Pipe and BTs painted blue.

T35N RL2E E 50 lks to Cor. S498 1976

Dated at	Rhinelander	, Wis., this	llth	day of	June	, 1976
Signature Hill	(County Surveyor, Register of Deeds, County of	Title Re	istered La	and Survey	or Registratio	n NoS <u>-4</u> 98
	(County Surveyor, Registe	red Land Surveyor,	or other duly au	thorized official	I)	
Office of Registe	er of Deeds, County of	Forest	?		, I hereby certify	that the within
instrument was	filed in this office for re	cord on the	22nd	day of	June	<u>, 19. 76</u>
at3:45o'cloo	ck					
Luce	ne Stat	LAMI	DOCUMENI	NUMBER	109497	