State of Wisconsin	RESTORATION OF LOST ORIGINAL GOVERNMENT SURVEY CORNER.
County of FOREST	SS. RESTORATION OF LOST ORIGINAL GOVERNMENT SURVEY CORNER.
I <u>NEAL SPERHAKE</u> 19 64 , I established t RANGE 13 EAST. Fourth F	he WEST QUARTER SECTION CORNER OF SECTION 25, TOWNSHIP 35 NORTH, Principal Meridian,
	as described hereon
	as established during the original survey of this township, as noted in rield notes for the original survey of T35N-R13E, 4th. p.m.
	and accessories I established to perpetuate the location of this corner:
-	l for the location of the corner I emplaced a:
	THREE FEET LONG, ONE INCH IN DIAMETER, WITH ALUMINUM CAP DENOTED AS, T35N 4 BTWN. 26 & 25 R13E SPERHAKE RLS 463 9/18/64."
The pipe is witnessed b	y:
Maple 15 S 83°E Hemlock 10 N 83°W	E 19 links. (SCRIBED 4S 25 NBT). V 4 links. (SCRIBED 4S 26 NBT).
Description as to how c	corner was located: No evidence of the original corner present. Thus, set by proportionate measurement. Since both the sections corners $\frac{1}{2}$ mile north and south have been previously established with a distance between them of 79.62 chains, the quarter corner was set 39.81 chains from either corner and on a straight line between them.
	29600
O = Corner monument restored	JAN 121965 JAN 121965 Annalisation Register of Poeds
	Resident witnesses Dated at Crandon , Wisconsin, this 12th day of January , 1965.
	Signature Registered Land Surveyor Registration No. 463
	Office xxx Forest County of Wisconsin,
	TOTOTOTALE VITAT PLATE I. CONSESSES ASSESSED ASS

4351326200

Index No.

___Title__Notary Public