EDTICIED		CODNED	RESTORATION
CKIILIED	LAND	CORNER	KE2 LOUATION

SS.	History of original	corner establishment:
-----	---------------------	-----------------------

State of Wisconsin	} ss.	History of original corner establishmen
t. Towart	, ss.	5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 -

Original	Subdivision	bν	James	Nowlin	June	2	_	June	12.	7 86
OT.TRITT	PUDGIATATOIL	Uy	o attito a	MOMTTII	o arra	_	_	o mie	129	TOO

36 Lks. NAIE N33W Sugar Sugar

Description of corner evidence found:

2" iron pipe 5' long with brass cap set by C.E. Walker in 1938 Tiou:

Description of monument and accessories I established to perpetuate the original location of this corner.

Left monument set by Walker

Ties:

Maple	6
Maple	16
Maple	6

N17E S51W

7.12 feet 26.43 feet



марте		S79W	31.57 Teet		WIS. OBERVERS SURVINGERS
Dated at Cra	ndon	, Wis., this151	hday of	January	1976
Signature Count	y Surveyor, Registe	Title Surveyor, or other	ner duly authorized offic	Regis	tration No\$=88.7
Office of Register of De	eds, County of	Fore	est	, I hereby c	ertify that the within
instrument was filed in	this office for red	cord on the	15.thday of.	Januar	y
at 3 o'clock Lugent	(Register of Deec	1s/	Docum a r	nt Number	108574

of Jar evidence o	t on the 9th uary 19.76, I the section
Township.	ections 26, 27, 34, 8
as describe	E, Fourth Principal Mend hereon; and that from this evi
as describ	ed a new monument and accesed hereon to perpetuate the or
	this corner.
Resident v	itnesses:
, 	
	
	SEC -
	SEC

O = Corner monument restored.