O = Corner monument restored.

State of Wisconsin

## CERTIFIED LAND CORNER RESTORATION

Index No. A 1

History of original corner establishment: Original corner established by Alfred Curtiss in 1858 from which yellow birch 16" bears N45°W 18 lks. and yellow birch 12" bears S60°E 10 lks. Corner reestablished by I.R. Ritter, County Surveyor, in 1921 while making retracement of section 33. Set new cedar post and made NBT's - fir 8" N45°E 6-1/2 lks. and fir 4" N60°W 20-1/2 lks.

Corner recovered by Ray Leigh, Consolidated Forester. Set  $1-1/2^{\prime\prime}$  iron pipe in place of Ritter's wooden post.

Description of corner evidence found: Recovered 1-1/2" iron pipe set by Ray Leigh. Old squared wood post was lying beside it.

No evidence of Ritter's OBT's.

Description of monument and accessories I established to perpetuate the original location of this corner.

Replaced 1-1/2" iron pipe with 2-1/2" Berntsen, A-1 Federal Monument, aluminum with magnet installed in cap and base. Pipe projects 18" above ground.

Cap stamped - S498

T37N R14E

NBT's - W. spruce 9" N56°E 94.5 lks. scribed 1/4 BT. W. birch 10" S59°E 91 lks. scribed 1/4 BT.

No other trees suitable for BT's. Pipe and NBT's painted blue.

T36N R14E 1975

Dated at	Argonne	, Wis., this	15th	day of	De	cember	, 19.75
	(County Surveyor, Register	-		_			
	er of Deeds, County of filed in this office for re						
it 2:30 o'clo	ock P. M.  M.  Tate			DOCUME NT		1084	
3 y	(Register of Dee		Depu	ty		- - - ·	