reby day MAXI ange lian, ence ories vinal
16

0 =	Corner	monument	restored	•
-----	--------	----------	----------	---

CERTIFIED LAND CORNER RESTORATION

Index No. X-16

History of original corner establishment:

In 1921, J.R. Ritter, Registered Land Surveyor, subdivided section 34. He set the E.C. 1/16 - no BT's - we found an old squared cedar post which bears S81°W 10.00 feet of our corner.

Description of corner evidence found:

Total distance from 1/4 corner between sections 34 and 35 to C 1/4 corner section 34 is 2615.664 feet at bearing N89-06-46W.

Set E.C. 1/16 1307.832 feet intermediate.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1-1/2" iron pipe with 2" diameter brass cap - stamped: Projecting 18" above ground.

Marked NBT's:

Cedar 6" S54 W 22.76 feet
Black Spruce 7" N49 W 20.20 feet
scribed 1/16 - B.T.

T37N R14E EC 1/16 S | 34

S1537-1981

Dated at	Rhinelander	, Wis., this	23rd	day of	June	19.81
Signature	Daniel K. Pleage	Title Rep	gistered	Land Surve	yor Registratio	on No. 1537
J	(County Surveyor, Regis	tered Land Surveyor	, or other du	ly authorized offi	cial)	
Office of Reg	gister of Deeds, County of	Fores	t		, I hereby certify	y that the within
instrument v	was filed in this office for r	ecord on the	lst	day of	July	19 8L
at 8:30 o	clock A. M.			-		•
<u></u>	0	temes			DOCUMENT NO.	_
	(Register of De	eds)			12004	
By		· · · · · · · · · · · · · · · · · · ·	Deput	y		