location of this corner.

Resident witnesses:

State of Wisconsin

County of Forest

Philip T. Hansen , do hereby

certify that on the 2nd day

of December, 19.77, I found

evidence of the  $\frac{N}{1/16}$ 

corner of Section 16 - 17

Township......37......, North, Range

15 East Fourth Principal Meridian,

as described hereon; and that from this evidence

as described hereon to perpetuate the original

I established a new monument and accessories

O = Corner monument restored.

## CERTIFIED LAND CORNER RESTORATION

Index No. K- 9

History of original corner establishment:

Recovered an old corner which had been accepted as corner for many years marked by cedar picket. Set new 1" iron pipe with 2" brass cap. New corner established by J. Resvick, Forest Service surveyor. Ran line from NW corner Section 16 south to SW corner. Established 1/4 corner at 2636.13 feet. Set hub for N 1/16 at 1318.08 ft. intermediate.

Description of corner evidence found:

Recovered hub at 1318.08 feet.

Description of monument and accessories I established to perpetuate the original location of this corner.

Moved 1" iron pipe with 2" brass cap to new position at hub. Cap stamped:

Monument projects 18" above ground.

Marked NBTs - Sugar 5" N71°E, 33.3 feet
Sugar 7" S14°W, 41.4 feet

S498 T37N R15E N 1/16 17 16

CPI-1976

Dated at Rhinelander	Wis., this 16th	day of	September	19.76
Signature Millio Hansen.  (County Surveyor, Registered	Title Registered	Land Surveyor	rRegistra	ation No. S-498
Office of Borister of Doods County of	Forest		I hereby cer	tify that the within 1976
Instrument was filed in this office for reco	_	DOCUMENT	NUMBER 1	10502
Register of Deces)  By	Deputy	 Y		