S1682 **-** 1984

History of original corner establishment:

No evidence of any previous corner.

Description of corner evidence found:

Total distance from 1/4 corner between sections 19 & 30 to C 1/4 Section 30 is 2622.901. Set NC 1/16 1311.45' intermediate.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1" iron pipe with 2" diameter alloy cap stamped: S1682 Marked NBTs: Cedar 12" W88N 23.74 CN 1/16^S 30 Cedar 13" 34.48 N28W R14E

Dated at Rhinelander	, Wis., this	6th	day of	February	. 19 85
Signature Son Suler	Title Re	egistered	Land Surve	yor Registra	tion No. 1682
(County Surveyor, Registered	d Land Surveyo	or, or other duly	authorized offic	cial)	
Office of Register of Deeds, County of	Fo	rest		I hereby cer	tify that the within
instrument was filed in this office for reco	rd on the	22nd	day of	February	
at 2:15 o'clock P. M.			· ·	-	•
				~	

Saul Mochentrenner (Register of Deeds)

State of Wisconsin > S\$. County of Forest Glen Barker certify that on the 27th day of December , 1984 , Ixonox established NC 1/16 corner of Section 3014 East, Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner. Resident witnesses: BARKERN. Spiess S-1682 CRANDON ...Lundt.

T38N		Ŗ14E.		
]	 	
j ,	ا ا س	NC 1/16	1	
 	G) _	 	
	s l	30] [
	-		<u> </u>	
 	 		' ! !	
-	i	' -	· · · · ·	
1	i 1			
	 1		! !	

O = Corner monument restored.