Tamarack stump. 6 ins. when blazed. Lower part of blaze has overgrowth with ax notch as were made on scribed faces. The rest of the blaze has been sawed off. Point from this stump agrees with distance across point.  Description of monument and accessories I established to perpetuate the original location of this corner:  At a point Sh6°W, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked:  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears S86°E, 10.22 ft. or 15.485 lks.  A black spruce 4 ins. diam., bears S39°E, 17.01 ft. or 25.772 lks.  Corner is on the edge of shore in water, rocks are piled around pipe.  Silland Scribes are piled around pipe.  Resident witnesses.  Dated at Rhime lander.  Wisconsin, the Salvandar SURVEYOR.  (County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOUMENT No. 98053		FIED LAND CORNER RES	STORATION	
L Jenn Resvick do hereby certify that on the 2nd day of October 19.69, found evidence of the Var21e Lake Mest side of Point Reference of Section 6.  Township J.7 M Range 19.5 E. Pount Principal Meridian, as described reference and that from this evidence I established a new monument and accessories as described hereon to pertent the original location of this corner.  Description of original monument and accessories and subsequent restorations:  Township lines surveyed in 1857 by Artemus Curtis. 80.43 ch. west between Section 6 and 31. Set post for Meander Corner.  Tamarack of ins. bears NH6°E 11 lks.  Spruce 5 ins. bears NH6°E 11 lks.  Spruce 5 ins. bears ST7°E 21 lks.  Description of corner evidence found.  Tamarack stump, 6 ins. when blazed. Lower part of blaze has overgrowth with ax notch as were made on scribed faces. The rest of the blaze has been sawed off. Point from this stump agrees with distance across point.  Description of monument and accessories I established to perpetuate the original location of this corner.  At a point SH6°W, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked:  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears S390E, 10.22 ft. or 15.165 lks.  A black spruce 4 ins. diam., bears S390E, 10.22 ft. or 15.165 lks.  A black spruce 4 ins. diam., bears S390E, 17.01 ft. or 25.772 lks.  Signatur. Jean Resvick.  Wisconsin, description of the surveyor or other day authorized difficing Surveyors Registered Lond Surveyor, or other day authorized difficing Surveyors Registration No. 98053	State of Wisconsin			
I Jean Resvick do hereby certify that on the 2nd. day of October 19 69 found evidence of the VanZile Lake West gide of Point Nomer of Section 6 forwards 37. N Range 15. E Fourth Principal Meridian, as described tereor, and that from this evidence I established a new monument and accessories as described hereon to perbetuate the original location of this corner:  Description of original monument and accessories and subsequent restorations:  Township lines surveyed in 1857 by Artenus Curtia. 80.h3 ch. west between Section 6 and 31. Set post for Meander Corner.  Tamarack 6 ins. bears Nh60s hi lks. Spruce 5 ins. bears S770s 21 lks.  Description of corner evidence found:  Tamarack stump, 6 ins. when blazed. Lower part of blaze has overgrowth with ax notch as were made on scribed faces. The rest of the blaze has been sawed off. Point from this stump agrees with distance across point.  Description of monument and accessories I established to perpetuate the original location of this corner:  At a point Sh60w, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked:  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears \$390E, 17.01 ft. or 25.772 lks.  1811	County of Forest			
Township lines surveyed in 1857 by Artemus Curtis.  31. Set post for Meander Corner.  Tamarack 6 ins. bears Nh6°B hl lks. Spruce 5 ins. bears S77°E 21 lks.  Description of corner evidence found:  Tamarack stump. 6 ins. when blazed. Lower part of blaze has overgrowth with ax notch as were made on scribed faces. The rest of the blaze has been sawed off. Point from this stump agrees with distance across point.  Description of monument and accessories I established to perpetuate the original location of this corner:  At a point Sh6°W, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked.  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears S86°E, 10.22 ft. or 15.485 lks.  A black spruce 4 ins. diam., bears S39°E, 17.01 ft. or 25.772 lks.  S311  Corner is on the edge of shore in water, rocks are piled around pipe.  Resident witnesses.  Dated at RAINE Lander.  Wisconsin, the Colons of the Colons o	I Jean Resvick , do I found evidence of the VanZile Lak Township 37 N hereon; and that from this evidence I	Range 15 E established a new monument	, Fourth Principal M	leridian, as described
Tamarack 6 ins. bears Nh6°E hi lks.  Spruce 5 ins. bears S77°E 21 lks.  Description of corner evidence found:  Tamarack stump. 6 ins. when blazed. Lower part of blaze has overgrowth with ax notch as were made on scribed faces. The rest of the blaze has been sawed off. Point from this stump agrees with distance across point.  Description of monument and accessories I established to perpetuate the original location of this corner:  At a point Sh6°W, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked.  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears S86°E, 10.22 ft. or 15.165 lks.  A black spruce h ins. diam., bears S39°E, 17.01 ft. or 25.772 lks.  S8N R15E  S3N  Corner is on the edge of shore in water, rocks are piled around pipe.  Resident witnesses.  Dated at RAins lander.  Signatur Jean Resvick.  Title Gadastral Surveyor  (County Surveyor Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOCUMENT No. 98053	Description of original monument and	accessories and subsequent re	estorations:	
Tamarack stump. 6 ins. when blazed. Lower part of blaze has overgrowth with ax notch as were made on scribed faces. The rest of the blaze has been sawed off. Point from this stump agrees with distance across point.  Description of monument and accessories I established to perpetuate the original location of this corner:  At a point Sh6°W, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked:  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears S86°E, 10.22 ft. or 15.485 lks.  A black spruce 4 ins. diam., bears S39°E, 17.01 ft. or 25.772 lks.  Corner is on the edge of shore in water, rocks are piled around pipe.  Silland Scribes are piled around pipe.  Resident witnesses.  Dated at Rhime lander.  Wisconsin, the Salvandar SURVEYOR.  (County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOUMENT No. 98053	31. Set post for Meander Corn Tamarack 6 ins.	er. bears N46°E 41 lks.	0.43 ch. west betwe	en Section 6 and
At a point Sh6°W, 27.06 ft. from tamarack stump set a 2 in. inside diameter galvanized wrought iron pipe, 5 ft. long filled with concrete with a brass cap marked:  From which the following new blazed and scribed bearing trees bear.  A white pine, 17 ins. diam., bears S86°E, 10.22 ft. or 15.485 lks.  A black spruce 4 ins. diam., bears S39°E, 17.01 ft. or 25.772 lks.  Corner is on the edge of shore in water, rocks are piled around pipe.  Corner is on the edge of shore in water, rocks are piled around pipe.  Resident witnesses.  Dated at Rhime lander  Wisconsin, the standar of the County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOCUMENT No. 98053	were made on scribed faces. T	he rest of the blaze has	<del>-</del>	
Corner is on the edge of shore in water, rocks are piled around pipe.  Cols 6 T37N 1969 S-802  Resident witnesses.  Dated at Rhime lander  Wisconsin, test should be surveyor  (County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOCUMENT No. 98053	At a point S46°W, 27.06 ft. from which the fact of the spring of the spr	om tamarack stump set a filled with concrete wit ollowing new blazed and e, 17 ins. diam., bears	2 in. inside diame th a brass cap mark scribed bearing tr S86°E, 10.22 ft. o	ter galvanized ed: ees bear. r 15.485 lks.
Resident witnesses.  Dated at/Rhime lander Wisconsin, this fire day of the land 19.62.  Section 6  Signature Jean Resvick Title Cadastral Surveyor (County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOCUMENT No. 98053	M.C/S 6 T37N 1969	edge of shore in water,	CONTRACTOR OF THE PARTY OF THE	CONSEAN F. ESVICK
Section 6  Signature Jean Resvick  (County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOCUMENT No. 98053	Re	sident witnesses		WIS. OS
(County Surveyor, Registered Land Surveyor, or other duly authorized official)  Surveyors Registration No. S-802  DOCUMENT No. 98053				SUR
	Section o Sig			
	Su	veyors Registration No. 5-80	DOCUI	ENT No. 98053
Office of Register of Deeds County of Forest			_	
I hereby certify that the within instrument was filed in this office for record on the 22nd day of May 19.70, and was filed in Book	Ih	ereby certify that the within in the 22nd day of Mar	instrument was filed in 70	this office for record
= Corner monument restored NoPage Noof County Records.	Corner monument restored No	Page No.	ار الماركof County Re	cords.
Signature Signature States Title Register of Deeds  Township 37 North Range 15 East Section 6 Index No.A-1,2 Page No.	Sig	nature Light Section 6	Tritle Regi	ster of Deeds