FILED ON: 12/19/2024 03:53 PM

CORTNEY BRITTEN CLEEREMAN REGISTER OF DEEDS

FOREST COUNTY WI

PAGES: 1

INDEX#: A 17

T.38N. T.37N.

## U. S. PUBLIC LAND SURVEY MONUMENT RECORD

A-E 7.08(3)(a) Identity of corner: Southeast Corner Section 34, Township 38 North, Range 16 East of the Fourth Principal Meridian, Town of Fence, Florence County,

WISCRS - FOREST COUNTY N: 626,120,835 USft (XXX,XXX,XXX) E: 947,579.053 USft (XXX,XXX,XXX) Datum: NAD83 (2011) **GNSS Method RTK GNSS Control WISCORS VRS** 

The coordinate value shown has been verified by the average of two or more GPS observations

at a markedly different time. Coordinates shown in parenthesis are previously published values.

A-E 7.08(3)(b)

Original Surveyor: Artemas Curtis - September 1857 to October 1857 Tamarac 5 - N 58° W, 108 Links, Tamarac 5 - N 64° E, 13 Links, Tamarac 5 - S 22° W, 98 Links

See Plat of Survey for Certified Land Corner Restoration & Establishment - C0999 (Florence Co.) - 1986 - Surveyor 1634 - Gary Lee Pisoni THENCE:

April 15, 2024 - In performing the 2024 - Forest County - "PLSS Corner Remonumentation and GPS Services" project, I found a 2.5" diameter aluminum pipe monument with a 3.25" diameter aluminum cap stamped to identify the corner. The monument is in a spruce swamp, and is ±4" below the water surface. I also found 1 of Pisoni's bearing trees dead and standing. l established 4 new reference monuments as shown below.

A-E 7.08(3)(c)(d) Plan view of corner with references to at least 4 witness monuments.

Bearings listed to the nearest second are referenced to the: Wisconsin County Coordinate Reference System, FOREST County Zone. All other bearings are magnetic.

New B.T. - 3" Spruce Horizontal nail, set in SW side ±3' above grade. New Survey Marker sign, set.

New B.T. - 3" Spruce Horizontal nail, set in SE side ±3' above grade.

New Survey Marker sign, set. (N 79° E 60.60′)

Old B.T. - 4" Tamarack - dead - not measured. Old B.T. sign, found.

New B.T. - 3" Spruce Horizontal nail, set in NW side ±3' above grade. New Survey Marker sign, set.

New B.T. - 3" Spruce Horizontal nail, set in SW side ±3' above grade.

New Survey Marker sign, set.

## LEGEND

Monument sizes = outside diameter measurements.

Steel sign post, found ±1.3 feet NW of corner

Galvanized nail, set or nail found as shown

A-E 7.08(3)(e) 1857 Surveyor set a post, 1986 Surveyor found a 2 1/2" diameter aluminum pipe monument. In 2024, I found a 2.5" diameter aluminum pipe monument with a 3.25" diameter aluminum cap stamped to identify the corner.

A-E 7.08(3)(f) I accept this monument in good faith as a FOUND PERPETUATED LOCATION of the comer. A-E 7.08(3)(g)(h) This corner was not determined through lost-corner-proportionate methods.

A-E 7.08(3)(i) I, Jeffrey L. DeMuth, Professional Land Surveyor No. S-2656, hereby certify that the corner location on this record was determined by me or under my direction and control, and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge, and belief.

April 17, 2024



43816340000

SIGNATURE