



Stock No. 26273

Sheet 2 of 6

SURVEY NOTES

This survey was made by Gary L. Pisoni, a Registered Land Surveyor in the State of Wisconsin, for the U.S.D.A., Forest Service, for the purpose of recovering, restoring, establishing, marking, and perpetuating the corners and boundary lines of U.S. Government Land on the perimeter and within Section 13, Township 36 North, Range 16 East, Fourth Principal Meridian, Forest County, State of Wisconsin, as shown on the plat map herewith.

The Original Government Township Lines were done Artemas Curtis, U.S. Deputy Surveyor in September of 1857. The original Government Sub-division of this township was done by James McBride, U.S. Deputy Surveyor in July of 1858.

The bearings between corner positions are true bearings referenced to the West One-Half of the South section line of Section 11, as determined by a solar observation by Charles F. Clark of Coleman Engineering Co. from a Plat of Survey of 1991 of Section 11. All distances shown thereon are in feet and hundredths of feet. The control traverse was measured by use of an electronic distance measuring equipment.

The accuracy of this survey exceeds the State requirements of 1 in 3000.

The field notes and a copy of the Plat of Survey are on file in the Forest Supervisor's Office at Rhinelander, Wisconsin.

CORNERS RECOVERED AND RESTORED1. Northwest Section Corner

In 1968, Jean F. Resvick, RLS (U.S.F.S.) restored the corner position from original bearing tree stump holes and an iron pipe found at the corner position.

1968 Corner references:

Spruce	4"	N 10°W	93.25 feet
Spruce	4"	S 84°E	56.00 feet
Spruce	4"	S 02°W	38.20 feet
Aspen	6"	N 73°W	49.37 feet
4 X 4 Cedar Post		N 42°E	1.70 feet

2. North Quarter Corner

In 1982, M.E. Stefan, RLS (U.S.F.S.) restored the corner position from a recovered flue pipe set by Goodman Lumber Co. in 1927.

1982 Corner References by M.E. Stefan:

White Spruce	12"	S 79°E	41.03 feet
White Spruce	10"	S 09°E	64.30 feet
White Spruce	18"	S 85°W	68.19 feet
Aspen	8"	N 50°E	10.77 feet
Steel Sign Post		East	1.40 feet

3. East Sixteenth Corner between Sections 12 and 13

Found a 2 1/2" diameter Aluminum monument with a stamped aluminum cap set by Charles F. Clark, RLS in 1991.

1991 Corner References by Charles F. Clark:

Balsam	4"	S 87°E	6.44 feet
Balsam	6"	South	14.03 feet
Balsam	4"	S 85°W	6.06 feet
Steel Sign Post		Northeast	1.07 feet

4. Northeast Section Corner

In 1968, Jean F. Resvick, RLS. restored the corner position from a recovered 4" diameter iron pipe with Marinette County brass cap set by Gould and Hammes in a 1936 and 1937 survey.

1968 Corner References:

Red Pine	11"	S 82°E	8.92 feet
Red Pine	8"	S 17°W	16.60 feet
Red Pine	10"	N 82°W	35.65 feet

In 1991, Charles F. Clark Established Additional Corner References:

Red Pine (existing)	13"	N 81°W	35.72 feet
Red Pine (existing)	13"	S 84°W	8.85 feet
Red Pine (existing)	14"	S 18°W	16.62 feet
Red Maple (new)	5"	N 05°E	17.83 feet
Steel Sign Post (new)		Northwest	1.84 feet

5. North Sixteenth Corner between Sections 13 and 18

In 1968, Jean F. Resvick, RLS restored the corner position from a recovered 4" squared post set by Gould and Hammes in a 1936 and 1937 survey. Resvick replaced point of rotted post with a 2" inside dia. iron pipe, 5 feet long, filled with concrete, flanged on bottom, with a brass cap.

1968 Corner References:

Basswood	14"	N 55°W	34.77 feet
Elm	6"	N 75°E	3.09 feet

1993 Corner References:

Basswood Exists	20"	N 57°W	34.39 feet
Sugar Maple New	10"	S 10°E	10.44 feet
Steel Sign Post		East	1.65 feet

6. East Quarter Corner

In 1968, Jean F. Resvick, RLS restored the corner position from a recovered 4" iron post with a Marinette County brass cap set by Gould and Hammes in a 1936 and 1937 survey.

1968 Corner References:

Ash	5"	N 36°W	34.90 feet
Spruce	9"	N 22°E	44.13 feet
4 X 4 Cedar Post		N 34°E	1.20 feet

1993 Corner References:

White Spruce Exists	14"	N 20°E	44.40 feet
Cedar Post Exists	4 X 4	N 15°E	1.60 feet
Black Ash (New)	12"	S 83°E	78.74 feet
Black Ash (")	7"	S 84°W	51.04 feet
Black Ash (")	5"	N 50°W	39.97 feet
Steel Sign Post	6'	S 58°E	1.00 feet

7. Southeast Section Corner

In an October 1936 - May 1937 survey, F.P. Gould & B.F. Hammes, Deputy County Surveyors, restored the corner position from a recovered hardwood post, 2" iron pipe and four sugar maple stumps that checked for B.T.'s showing axe marks.

1993 Corner References:

Sugar Maple	7"	N 44°E	27.80 feet
Sugar Maple	7"	S 34°E	12.45 feet
Sugar Maple	8"	S 38°W	12.19 feet
Sugar Maple	8"	N 40°W	18.81 feet
Steel Sign Post	6'	West	0.90 feet

Stock No. 26273

Sheet 4 of 6

8. South Quarter Corner

In 1982, Milo E. Stefan, RLS restored the corner position from a recovered 3/4" x 36" iron rod as local evidence. Iron rod matched stump holes at bearing and distance of original bearing trees. Stefan replaced iron rod with 2" aluminum pipe monument with a stamped tablet at the corner position.

1982 Corner References:

Sugar Maple	6"	S 01°E	11.20 feet
Sugar Maple	6"	S 53°W	21.81 feet
Yellow Birch	8"	N 30°W	29.62 feet
Steel Sign Post		West	1.50 feet

9. Southwest Section Corner

In 1988, John Schulke, RLS found the corner as described in Milo Stefan's field notes of 1982. Milo Stefan found an iron bolt and replaced it with a 2 1/2 inch x 36 inch aluminum monument with a stamped cap.

1982 Milo Stefan's Corner References:

Basswood	18"	N 08°E	46.80 feet
Sugar Maple	6"	N 89°E	9.64 feet
Sugar Maple	5"	N 48°W	37.55 feet
Steel Sign Post		West	1.30 feet

1988 Corner References:

Basswood	20"	N 15°E	46.78 feet
Sugar Maple	7"	N 89°E	9.57 feet
Sugar Maple	6"	N 39°W	37.45 feet
Sugar Maple	6"	N 45°E	43.85 feet
Steel Sign Post		West	1.30 feet

10. West Quarter Corner

In 1982, Milo Stefan restored the corner position from a 2 1/2 foot flue pipe set by Goodman Lumber Co. in 1926. Stefan replaced the flue pipe with a 2" dia. aluminum pipe monument with stamped tablet.

1982 Corner References:

Black Cherry	6"	N 53°E	29.23 feet
Black Cherry	6"	S 02°W	23.70 feet
White Spruce	6"	N 23°W	36.11 feet
Steel Sign Post		North	3.90 feet

1994 Corner References:

Black Cherry (Dead)		N 53°E	
Black Cherry Exists	8"	S 02°W	23.70 feet
White Spruce	9"	N 23°W	36.11 feet
Elm (New)	6"	N 64°E	12.28 feet
Black Cherry (New)	7"	N 71°W	18.93 feet

CORNERS ESTABLISHED1. North Sixteenth Corner between Sections 13 and 14.

Corner position established at midpoint and on line between the Northwest Section corner and West Quarter corner of Section 13.

Corner references:

Ash	6"	N 06°W	20.08 feet
Spruce	10"	N 76°E	27.55 feet
Steel Sign Post		S 45°E	0.69 feet

2. Center North Sixteenth Corner

Corner position established at midpoint and on line between the North quarter corner and the Center quarter corner.

Corner References:

Red Maple	8"	N 45°E	24.81 feet
White Spruce	6"	S 10°W	4.15 feet
Steel Sign Post		West	0.95 feet

3. Northwest Sixteenth Corner

Corner position established at the intersection of the straight lines between opposing sixteenth corner positions on the perimeter of the Northwest quarter of Section 13.

Corner References:

Sugar Maple	11"	S 56°W	24.12 feet
Sugar Maple	5"	N 60°W	29.51 feet
Steel Sign Post		North	1.32 feet

4. Center West Sixteenth Corner

Corner position established at midpoint and on line between the West quarter corner and the Center quarter corner.

Corner References:

Red Maple	6"	S 20°E	35.90 feet
Black Cherry	11"	S 45°W	34.34 feet
Steel Sign Post		S 64°E	0.85 feet

5. Center Quarter Corner

Corner position established at the intersection of the straight lines between opposing quarter corner positions on the perimeter of the Section.

Corner References:

Cedar	15"	N 19°E	48.68 feet
Cedar	14"	S 14°E	19.75 feet
Steel Sign Post		East	0.77 feet

6. Center South Sixteenth Corner

Corner position established at midpoint and on line between the Center quarter corner and the South quarter corner.

Corner References:

Sugar Maple	7"	S 21°W	36.16 feet
Red Maple	6"	N 82°W	42.77 feet
Steel Sign Post		N 24°W	0.60 feet

7. South Sixteenth Corner between Sections 13 and 14

Corner position established at midpoint and on line between the Southwest Section corner and the West quarter corner.

Corner References:

Spruce	8"	N 03°E	90.55 feet
Balsam	7"	N 31°E	108.91 feet
Steel Sign Post		West	0.90 feet
Steel Sign Post		South	1.58 feet

Stock No. 26273

Sheet 6 of 6

SURVEYOR'S CERTIFICATE

State of Wisconsin) ss
 County of Forest)

I, Gary L. Pisoni, a Cadastral Surveyor, and a Registered Land Surveyor in the State of Wisconsin, hereby certify that I have surveyed and sub-divided Section 13, Township 36 North, Range 16 East, Fourth Principal Meridian, State of Wisconsin.

The plat map and survey notes herewith are a correct representation of the land surveyed and divided. I have surveyed and sub-divided said section in accordance with the rules for the survey of public lands and with the statutes of the State of Wisconsin.

Date of Survey: 1993-94

Gary L. Pisoni
 Cadastral Surveyor
 R.L.S. State of Wisconsin
 Certificate S-1634

