**MAP OF SURVEY** Bearings are referenced to: North 1/4 Corner Section 13 The Wisconsin County Coordinate LANDS BEING PART OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4, per U.S.P.L.S. Monument Record. Reference System. Found & verified Forest County SECTION 13, TOWNSHIP 37 NORTH, RANGE 12 EAST, FOURTH PRINCIPAL MERIDIAN, FOREST County Zone, Aluminum Monument. and the South line of the TOWN OF HILES, FOREST COUNTY, WISCONSIN See updated U.S.P.L.S. FOREST CO SURVEYOR SW 1/4 of Section 13 Monument Record. DESCRIBED IN DOCUMENT #233056 & #238867 FILE # 371713-20140312 SURVEYOR'S CERTIFICATE DATE 05/74/7071L I, Jeffrey L. DeMuth, Professional Land Surveyor S-2656 of the State of Wisconsin, do hereby certify to my clients, Mark and Amy Cigan, the owners and under whose direction this survey was West 1/4 Corner Section 13 performed, that I have surveyed, mapped, and described those lands described in document per U.S.P.L.S. Monument Record S 87°41'24" E 2690.63' number 233056 and 238867; being part of the Southeast 1/4 of the Southwest 1/4, Section 13, Found & verified Forest County Township 37 North, Range 12 East, Fourth Principal Merdian, Town of Hiles, Forest County, Aluminum Monument. East - West 1/4 Line S 87°41'10" E 2779.82' See updated U.S.P.L.S. Wisconsin Monument Record. Center 1/4 Corner Being more particularly described for mapping purposes as follows: East 1/4 Corner Section 13 Commencing at the South 1/4 corner of Section 13, thence, N 00°55'06" E, per U.S.P.L.S. Monument Record. NE 1/4 - SW 1/4 along the North-South 1/4 line of said section, 50.00 feet to the north Found & verified Forest County right-of-way line of State Trunk Highway 32, and the POINT OF BEGINNING Unplatted Lands - Doc. #241027 Aluminum Monument. of lands surveyed. See updated U.S.P.L.S. Monument Record. Thence, leaving said 1/4 line, and along said right-of-way S 89°38'23" E 1333,55' line the following courses: N 83°51'11" W, a distance of 165.55 feet, S 88°30'18" W, a distance of 309.79 feet, LEGEND Southwest S 84°13'16 W, a distance of 524.63 feet; Thence, leaving Center - South 1/16 Corner Monument sizes = outside diameter measurements. 1/16 Corner said right-of-way line, S 01°37'19" E, a distance of 34.97 feet to the south 0.75" diameter X 18" long iron rod. line of the Southwest 1/4 of Section 13; Thence, S 88°22'41" W, a distance Ш weighing 1.5 lbs. per lineal foot, set of 328.49 feet, to the West 1/16th corner; Thence, leaving said south line, 8 (a) 1.5" diameter iron pipe, found N 00°22'21" E, along the east line of the Southwest 1/4 of the Southwest 1/4 O 2" diameter iron pipe, found of Section 13, a distance of 1200.37 feet to the Southwest 1/16th corner: Thence, leaving said east line, S 89°38'23" E, along the south line of the Iron pipe, found as noted Northeast 1/4 of the Southwest 1/4, a distance of 1333.55 feet to the U.S.P.L.S. monument, as noted S Center South 1/16th corner; Thence, leaving said south line, △ Computed position, not set S 00°55'06" W, along the North-South 1/4 line, a distance of R/W marker - Steel fence post, found 1104.67 feet to the POINT OF BEGINNING. O ( ) Previously recorded data Said parcel contains 34.50 acres of land more or less, including Centerline those lands described in document number 238867. SE 1/4 - SW 1/4 P.O.B. Point of Beginning M M Doc. #233056 R/W Right-of-Way line Said parcel is subject to easements, ±33.47 ACRES restrictions, reservations, rights-of-way, Doc. Document ±1,457,855 S.F. and claims, if any. U.S.P.L.S. United States Public Land Survey R/W AREA ≥ S.F. Square feet ±0.27 ACRES That this map is a true and correct ±11.567 S.F. representation of the exterior Doc. #233056 & Doc. #238867 ANTIHITION boundaries of land surveyed, and COMBINED AREA that I have fully complied with SW 1/4 - SE 1/4 LESS R/W Chapter A-E 7 of the SW 1/4 - SW 1/4 ±34.23 ACRES Unplatted Lands - Doc. #213900 Wisconsin Administrative Code. ±1.491.264 S.F. Unplatted Lands - Doc. #241027 to the best of my knowledge and belief. N 88°29'05" E Doc. #238867 ±1.03 ACRES March 22, 2024 Southwest Corner Section 13 per Record & Certification of U.S. Public Land Survey Control Station. (N 84°48'20" W) (S 87°29'24" W) Set Berntsen steel Survey Mark Spike from (S 83°13'16" W 526.39') N 83°51'11" W S 88°30'18" W reference monuments. P.O.B. S 84°13'16" W 524.63 30.02 See updated U.S.P.L.S. 88°29'05" W 327.26 R/W Southeast Corner Section 13 994.86' STATE TRUNK HIGHWAY 32 Monument Record. 150.00 - 50 00' per U.S.P.L.S. Monument Record. South line SW 1/4 - Section 13 Found & verified Mag nail shaft. Doc. #164067 S 88°22'41" W 2646.70' See updated South 1/4 Corner Section 13 per U.S.P.L.S. Monument Record. R/W VARIABLE R/W U.S.P.L.S. Monument West 1/16 Corner Set Berntsen steel Survey Mark spike from survey map R/W 371213-19990506. See updated U.S.P.L.S. Monument Record. Record