| ERTIFIED | LAND | CORNER | RESTORATION |
|----------|------|--------|-------------|

Index No. Q - 1

History of original corner establishment:



Description of corner evidence found:


FOUND NW AND SW CORNERS OF SECTION 19, BUT COULD NOT FIND W'14 CORNER OLD MARATHON COUNTY HIGHWAY NOTES SAID SECTION 19 WAS 80 CHAINS, OUR MEASURMENT WAS 5267.35 . THE YIG CORNER WAS SET AT 1316.84! SET R.R. SPIKE AT CORNER WAS SET 5-10-78 AND WITNESSED 9-21-78)

Description of monument and accessories I established to perpetuate the original location of this corner. 8 - NAIL SET IN POWER POLE - P.K. NAIL IN CULVERT 5/16 O - 1" x 30" IRON PIPE IN PLUG RIDE , RHE A - RAILROAD SPIKE 5, 24 19 2 50.00 O - 2" x 42" BLACK IRON PIPE WITH BRASS CAP NOTE: BRASS CAP SET ACROSS FROM PIPE WITH TRANSIT, ALL OTHER BEARINGS TO TIES TAKEN WITH RECON COMPASS. , Wis., this 3RD Dated at ANTIGO day of OCTOBER 1978 Signature No. 1542 Title REGISTERED LAND SURVEYOR Registration No. 1542 (County Surveyor, Registered Land Surveyor, or other duly authorized official) Office of Register of Deeds, County of, I hereby certify that the within (Register of Deeds)

| | State | of | Wisconsin |] |
|-----|---------|----|-----------|--------|
| Cou | inty of | L | Wisconsin | } SS |
| [| WESLE | (ا | TRADEWELL | , do l |

certify that on the day of MAY 19 78, I found evidence of the NORTHWEST corner of 5W'/4, 5W'/4, SECTION 19 Township 30 , North, Range 11 EAST Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Resident witnesses:



O = Corner monument restored.