163
MA
~
2.3
4
~
- 5
-
æ
C0.
MILLER
Ü
÷

CERTIFIED LAND CORNER RESTORATION


Index No. R-15

History of original corner establishment:

ORIGINAL CORNER ESTABLISHED BY JAMES WITHROW IN NOU- DEC, 1854.

Description of corner evidence found:

R.R. SPIKE Established by Dynamic Engineering. Used as Corner for Haw "s" improvement.



SET (2) 11/2" x 42" BLACK IRON PIPES WITH BRASS CAP MONUMENTS. Description of monument and accessories I established to perpetuate the original location of this corner.

L COCK	P C. C.I.		
4	WIT COR COR 50' SE	CAP Q SAN	WIT COR COR. 40' N
	5 1/4 COR SECT 22	QIZ R.R. SPIKE	S 1/4 COR SECT 22
X	T30N RIZE	30 10 HWY. 47	T30N + R12E
R		POWER	11-25-81
2	11-25-81	POLE OZ 1/2" BRASS CAP	-
	WFK	WP 8L Y 23-52	WFK

Dated at ELCHO	Wis., this as a day of woverbook, 19 91.
Signature William F. Reg (County Surveyor, Reg	Title COUNTY SURVEYOR Registration No. 1098 stered Land Surveyor, or other duly authorized official)
Office of Register of Deeds, County	of, I hereby certify that the within record on theday of, 19, 19
(Pagistar of F	loads)

..Deputy

Resident witnesses: M waldrogel

State of Wisconsin

I WILLIAM F. KELLY , do hereby certify that on the 25th day of Nov. , 19.81 , I found evidence of the 5 1/4 corner of SECT 22 Township. 30, North, Range

12 E , Fourth Principal Meridian,

as described hereon; and that from this evidence I established a new monument and accessories

as described hereon to perpetuate the original

County of LANGLADE

location of this corner.

T30N, R/2E	
-	
Į Ī I	
I / I	
1 1	

O = Corner monument restored.