

4321129 2000 2025

U.S. PUBLIC LAND SURVEY MONUMENT RECORD - LANGLADE COUNTY

Note: This form is intended and designed to fulfill all requirements of Wisconsin Administrative Code, Chapter A-E 7.08 U.S. Public Land Survey Monument Record (3)(a)(b)(c)(d)(e)(f)(g)(h)(i). An additional sheet may be added to if necessary to conform with said requirements.

(a) Corner Location:

Wisconsin Corner ID: 43211292000

Type of Monument: RR Spike

Location: East Quarter Corner

Section 29, Township 32 North, Range 11 East,

Town of Neva, Langlade County, Wisconsin

Langlade County Coordinates NAD83(2011):

Northing: 371763.93

Easting: 624939.10

RTK GPS direct observation

Calibrated to HMP DQ4953 (Lawrence Lake GPS)

3 position average on 5/2/2025



T32N-R11E

(b)(f)(g)(h) Description of monument found at this corner and if it was accepted, state all evidence (material, testimonial, occupational, plats, records, other monuments) used as a basis for accepting. If not accepted or if nothing was found, state evidence used as basis for establishing location. If reestablishment through lost corner proportionate methods, indicate all monuments, distances and directions used to establish. Indicate type of monument found or set and sign post.

- 9/1860 - H.C. Fellows - Set quarter section post, made references: sugar 12 S45°E - 15 links, elm 10 N80°W - 10 links.
- 2/2/1878 - Deleglise - FB 143 Pg 86 - At corner.
- 1879 - Deleglise - FB 144 Pg 29 - At corner for survey of Langlade Road.
- 10/6/1884 - B.F. Dorr - FB 25 Pg 17 Oneida County records - At corner post for Section subdivision.
- 3/15/1974 - William Kelly - Map#10028 - Shows corner, no monument description.
- 11/15/1988 - William Kelly - CSM V4 P150 - Found PK nail
- 12/01/1994 - Daniel Higginbotham - Map#40193 - Set RR Spike.
- 10/27/1997 - Daniel Higginbotham - CSM V7 P161 - Found RR Spike
- 12/27/2005 - Dave Tlusty - Map#30557 - Found RR Spike.
- 10/25/2015 - Timothy Rusch - Map#20004 - Shows a found 1" iron pipe, likely mislabeled.

5/5/2025 - Chad Besaw - Found and accepted a RR Spike approximately 0.2' below road surface. No previous tie sheet on file. RR spike matches distances to other corners of record and matches with Higginbotham's distance to a 1" iron pipe shown on Map#40193. Made references shown below.



Chad A. Besaw

6/6/2025

Date

(c)(d)(e) Plan view of corner with ties to at least 4 witness monuments. If in disagreement with previously established corner, show the distances between the two corners and also indicate the ties to the disputed corner.

