County of Langla	de ss.
I Raymond J.	Hallisy do hereby
certify that on the	3rd day 1/4 No. 41 P
of December	, 19 <u>,</u> I found
corner of 2 & 3	
Township 32	, North, Range
, F	ourth Principal Meridian
as described hereon; ar	nd that from this evidence
I established a new n	nonument and accessories
location of this corner.	o perpetuate the original
rocation of this corner.	
Resident witnesses:	
****	••••••
132 M	R12E
_ 1	
ļ	
Section .	Section
	
1 1	1
· .3	
1	
1	
1	
i	
) = Corner monument	restored.

State of Wisconsin

CERTIFIED	LAND	CORNER	RESTORATION
		COMMEN	NESTORATION

Index No. C - 17

History of original corner establishment:

32-12

Corner set in the 1930 resurvey.

Description of corner evidence found:

4" iron pipe with brass cap
Old ET's 22" Hard Maple N64E 13.5 Links

Description of monument and accessories I established to perpetuate the original location of this corner.

New PT's

le 852E 261 911

Hard Maple N74F 261
Hard Maple N21F 251

145 3 2 2 9-26-39

Signature (County Surveyor, Registered Land Surveyor, or other duly authorized official)

Registration No. S685

(Register of Deeds)

By.....Deputy