19 20 22 S 88'54'08" E S 86'18'44" E S 86'48'14" E N 86'56'41" E S 89'59'29" E S 88'07'57" E N 89°23'46" E 2632,46' 2722.09' 2687.40 2692.01 2717.05' 2685.08 2725.08 30 28 27 29

A CONTRACTOR OF THE STATE OF TH

NOTES: Dimensions based on traverse by Ayres Associates for C.T.H. "C". Bearings are referenced to the West line of the NW 1/4 of Section 29 which is assumed to bear N 0?00° E. Corner forms have been filed in the County Surveyors records for all monumented corner shown hereon.
Former surveyor Kelly made a note on several corner forms in this area that make mention of a survey in the 1970's by Wisconsin Public Service Corp. (WPS). I accurately spoke with a field representative from WPS. He indicated that any survey work they did was only preliminary work for a proposed power line route in the area. They did not set any section corners. This route was later abandoned. Any points they set were only traverse points, usually located at the approximate location for the section or quarter corners.

SOUTHWEST CORNER, SECTION 19

Set nail in patch over stone monument found, approximately 1.5' SW of Kellys "WPS" corner.

SOUTH QUARTER CORNER, SECTION 19

Set nail in patch over stone monument found. EAST QUARTER CORNER, SECTION 19

Found 3/4" iron rod in road as shown on corner form by Kelly dated 8/27/90.

SOUTHEAST CORNER, SECTION 19

Set RR spike from recovered Hutchinson 1/16 corner and 1/4 corner to the south.

SOUTH QUARTER CORNER, SECTION 20

Nail as previously shown on corner form by Kelly dated 10/21/81. EAST QUARTER CORNER, SECTION 20

Set rebar from previous broken glass evidence set by Hutchinson. SOUTHEAST CORNER, SECTION 20

Set PK over stone previously set by Hutchinson in 1912.

SOUTH QUARTER CORNER, SECTION 21

Set nail over 1" x 1 1/2" x 12" long, tapered "X" shaped iron
with 3" x 5 1/2" plat on top, found upright in ground, 3.5' below road

SOUTHEAST CORNER, SECTION 21

Set nail over stone found 40" in road. SOUTH QUARTER CORNER, SECTION 22

Nail set by Ayres from ties by Kelly. WEST QUARTER CORNER, SECTION 29

Found Hutchinsons gas pipe. Set new iron pipe with brass cap. This pipe found is approximately 38 feet north of Kellys "WPS" corner.

ND REGULA THIS DOCUMENT WAS CREATED ON EQUIPMENT THAT WAS PURCHASED GRANT RECEIVED FROM THE WISCON RECORDS

SCALE: 1" = 2000'

DRAWN BY: D. TLUSTY

REF. FILE:

DATE: 07/21/94

TOWN OF: PECK

TOWN CODE:

LOCATION: SEC. 19,20 & 21

SECTION:

TOWNSHIP: 32 RANGE: 10

DWG.#:/

CORSCTHC

LANGLADA CHINTY SURVEYORS OFFICE

BASED ON AYRES TRAVERSE & FIELD MEASUREMENTS

DAYE FILEN 3-16-851. AKML