

NORTHWEST CORNER
ESTABLISHED CORNER ON THE CENTER OF BLUEBELL ROAD
AND IN LINE WITH A FENCE TO THE NORTH. THIS POSITION
FITS WELL WITH FENCES 1/4 MI. NORTH & 1/4 MI. EAST.
SET 2" X 30" IRON PIPE WITH BRASS CAP IN ROAD.
N 369044.25
E 597143.06

NORTH QUARTER CORNER
SET GEARHEADED SPIKE, FROM TIES, OVER
STONE FOUND IN 1996.
N 368916.35
E 599867.70

N 368999.46
E 602545.31
NORTHEAST CORNER
SET IP WITH BRASS CAP OVER IRON ROD
PREVIOUSLY RECOVERED BY WES TRADEWELL IN 1979.

N 366287.31
E 597250.55

WEST 1/4 CORNER
ESTABLISHED ON AN EXTENSION OF A LINE FROM THE SW
CORNER EXTENDING NORTH, ALONG THE EXISTING FENCELINE
TO THE POINT OF INTERSECTION WITH THE EXTENSION
OF THE CENTER OF AN OLD ROADBED ON THE SOUTH
LINE OF THE SE-NW OF SECTION 34.
THIS POSITION WOULD WORK VERY WELL WITH A FENCE
CORNER AT THE 1/16TH CORNER TO THE SOUTH OF
HERE AND WOULD MAKE THE CW 1/16 CORNER FALL
IN THE CENTER OF SAID OLD ROADBED & IN LINE
WITH A VERY OLD FENCE TO THE SOUTH.

N 366298.29
E 599990.56

C 1/4 CORNER
ESTABLISHED ON THE N-S 1/4 LINE
AND ON THE CENTER OF OLD ROAD
TO THE WEST. THIS POSITION FITS
WITH A FENCE AT THE 1/16 CORNER TO
THE SOUTH, AND WORKS WITH A FENCE
CORNER AT THE 1/16 CORNER TO THE
EAST. SET BERNTSEN SN-1 NAIL

N 366290.24
E 602684.56
EAST QUARTER CORNER
SET A BERNTSEN SN-1 NAIL OVER IRON ROD PREVIOUSLY
SET BY WES TRADEWELL IN 1979.

N 363586.23
E 602827.19
SOUTHEAST CORNER
SET A GEARHEADED SPIKE OVER IRON ROD PREVIOUSLY
SET BY WES TRADEWELL IN 1979.

N 363552.32
E 597377.29
SOUTHWEST CORNER
ESTABLISHED ON AN EXTENSION OF A LINE FROM
THE SE CORNER TO THE S1/4 CORNER, EXTENDED
TO THE POINT OF INTERSECTION WITH THE EXTENSION
OF AN OLD FENCE FROM THE NORTH.

N 363569.38
E 600118.63
SOUTH QUARTER CORNER
SET GEARHEADED SPIKE FROM TIES OVER
STONE FOUND IN 1996.

COORDINATES SHOWN HAVE BEEN DETERMINED WITH
REAL TIME GPS SURVEY EQUIPMENT WITH AN ADVERTISED
ACCURACY OF 1 CM. COORDINATES ARE ON THE LANGLADE
COUNTY COORDINATE SYSTEM DEVELOPED BY THE WIDOT.
BEARINGS ARE LANGLADE COUNTY GRID BEARINGS.

NOT ALL 1/16 CORNERS WERE SEARCHED FOR TO DEVELOP THIS MAP.
THE BEARINGS AND DISTANCES HEREON ARE BETWEEN THE CORNERS SHOWN AND MAY OR
MAY NOT BE REPRESENTATIVE OF THE ACTUAL SECTION LINE BETWEEN THOSE CORNERS.
THERE MAY BE EXISTING 1/16 CORNERS THAT SHOULD BE HELD FOR SURVEY WORK.

-x-x-x- fencelines located

I, David E. Tlusty, Langlade County Surveyor, do hereby certify that I have made
a survey of the perimeter of Section 34, T32N, R10E as shown hereon for the purpose
of establishing and monumenting the West 1/4 corner, the Northwest corner and
the center of Section 34. Said corners determined as described above. This survey
was made under the presumption that Section 34 had been previously surveyed and
the record of said survey is not in the County Surveyors or Town records.
Corner monumentation record forms have been prepared for the corners shown and
described hereon. I further certify that this map is a true and correct representation
of said survey, and that this survey is correct to the best of my knowledge and belief.



August 7, 2000

David E. Tlusty, S-1390
Langlade County Surveyor

NO.	DATE	DESCRIPTION	BY

THIS DOCUMENT WAS CREATED ON LANGLADE COUNTY COMPUTER
EQUIPMENT THAT WAS PURCHASED WITH THE ASSISTANCE OF A
GRANT RECEIVED FROM THE WISCONSIN LAND INFORMATION BOARD.

LANGLADE COUNTY
LAND RECORDS & REGULATIONS DEPARTMENT

SCALE: 1" = 800'
DRAWN BY: D. TLUSTY
REF. FILE:
DATE: 07/24/00
TOWN OF: PECK
TOWN CODE:
LOCATION:
SECTION: 34
TOWNSHIP: 32
RANGE: 10
DWG. #: 343210